

Fish Tales Co.

www.fishtalesco.com.au


Job Card

Date:

Vessel	Job Type	Start Time	Finish Time
	<i>Quarterly Detail</i>		

Tasks	Action	Completed
Degrease and remove covers using Magic Sponge	<i>Degrease covers whilst on vessel using Magic Sponge, chammy dry and stow in safe place (away from waters edge or wind)</i>	
Degrease hard top or bimini	<i>Set up harness and safely stand on hard top or vantage point to Degrease Bimini. Ensure underside of domes and radar domes have been scrubbed. While up on hard top, high pressure wash nonslip and wash stainless steel fittings with StarClean (all undersides of instruments and fittings that can be seen from below)</i>	
Soap wash clears or windows/windcreens	<i>Ensure clears are washed using softwash tool or mitt. Ensure the whole clears section has been passed over with sort wash tool (if windy or hot work small sections to ensure soap doesn't dry on clears/glass as this will leave bad stewaking)</i>	
Degrease brows, side windows and superstructure	<i>When Degreasing the brow/superstructure and side windows ensure to soap</i>	






Fish Tales Co.

www.fishtalesco.com.au

Job Card

	<i>between superstructure overhang and windows (salt builds up in these areas, the salt cant be seen from the outside but is very visible from the inside)</i>	
Move or lift Kayaks, Lilypads and all yacht toys off deck	<i>When washing forward decks make sure all yacht toys have been lifted off the deck and soap washed underneath (If toys are salty, soap wash and notify us in comments)</i>	
Lift/open all deck hatches	<i>Open all hatches and Degrease out gutters, drains and inside of hatch lids (If scrubbing is required, use magic sponge or scotch brite)</i>	
StarClean Stainless bow rails and fittings	<i>Using a application pad, wash hand rails and fittings to remove all pitting and Tea staining (Ensure to wash underside or rails and inward side of fittings as rust usually hides in these areas)</i>	
Bleach non-slip High pressure wash	<i>When high pressure washing non slip use orange broom head (hard bristle) gurney and bleach (blue bottle) carefully scrub nonslip and keep all surrounding areas WET to prevent damaging covers etc</i>	
Degrease Bulwarks, in and out	<i>Degrease bulwarks using soft bristle brush. Be sure to check all gutters and inside bulwarks for grime build up. Usually black!</i>	
Degrease sunroof gutters	<i>Open sunroof and inspect gutters. Use a magic sponge</i>	




Fish Tales Co.

www.fishtalesco.com.au

Job Card

	<i>and degreaser to clean grime and chammy dry. (Note face of sunroof will have grime and mould)</i>	
Acid wash and brighten Teak deck, flybridge steps and anchor hatches	<i>Ensure all teak is completely soaked, apply acid and work across the grain of the teak. Once acid has completely absorbed into teak use rinse wand to remove ALL grey. Once this is complete, use brightener (Ensure there are no dark spots)</i>	
Rust and stain remove gelcoat around stanchions	<i>Walk around vessel and find any rust marks, mostly found around stanchions and stainless fittings and spray with rust and stain remover (open all hatches and hose out all hatch gutters)</i>	
Chammy vessel	<i>Chammy clears, glass and stainless steel using an absorbent chammy first following by a finishing chammy to ensure no water drops are left behind</i>	
Machine Wax Hard Top	<i>Set up harness and safely clip up extension lead. Machine wax all smooth areas, domes, radar bars and hatches. Wax all stainless fittings. (Ensure all wax has been removed, check from all angles)</i>	




Fish Tales Co.

www.fishtalesco.com.au

Job Card

Machine Wax Super structure, brow and Bulwarks	<i>Machine wax Super structure, brow and Bulwarks ensuring that cloudiness has been removed. Check from left, right and from below to ensure all wax has been absorbed.</i>	
Machine wax Cockpit and transom	<i>Machine wax transom and cockpit, Check from left, right and from below to ensure all wax has been absorbed.</i>	
Machine wax capping board for deck and gutters	<i>Machine wax all capping boards and around stanchions. Check from left, right and from below to ensure all wax has been absorbed.</i>	
Hand wax clears and glass	<i>Use applicator pad and wax glass and clears in and out. Check from left, right and from below to ensure all wax has been removed</i>	
Machine Wax Stainless steel	<i>Using an applicator pad, hand wax all stainless steel hand rails and fittings. Check from left, right and from below to ensure all wax has completely been removed</i>	
Final walk around	<i>Once all above tasks are complete, walk around vessel with a finishing chamois and microfiber to inspect vessel for any missed spots, wax left on or water drips</i>	



FishTales Co.

www.fishtalesco.com.au

Job Card

Comments:

.....
Detailer

.....
Signature